

# BARRIER LAMINATED FILM AND PRODUCTION THEREOF

Publication number: JP8099390

Publication date: 1996-04-16

Inventor: YAMAMOTO TORU; YOSHIDA SHIGEO

Applicant: YAMAMOTO TORU; IGARI MASAMICHI

Classification:

- International: **B05D3/02; B05D7/02; B05D7/24; B32B27/00; B32B27/08; B32B27/18; B32B27/28; B32B37/06; C08J7/04; B05D3/02; B05D7/02; B05D7/24; B32B27/00; B32B27/08; B32B27/18; B32B27/28; B32B37/06; C08J7/00; (IPC1-7): B32B27/28; B05D3/02; B05D7/02; B05D7/24; B32B27/00; B32B27/08; B32B27/18; B32B31/26**

- European:

Application number: JP19940228343 19940922

Priority number(s): JP19940228343 19940922; JP19940183702 19940804

Report a data error here

## Abstract of JP8099390

**PURPOSE:** To obtain a laminated film having excellent hot water resistance and gas barrier properties.

**CONSTITUTION:** A laminated film consists of a base material film composed of a thermoplastic resin and at least one composite polymer layer composed of a straight chain composite polymer layer composed of a random copolymer based on ethylene/vinyl alcohol obtained by the polycondensation of a compsn. containing an alkoxysilane, a silane coupling agent and an ethylene/vinyl alcohol copolymer due to a solgel method and laminated to at least the single surface of the base material film.

Data supplied from the **esp@cenet** database - Worldwide